

## DT Series

# DT Series

The DT series is a multi-functional Touch system specifically for retail & hospitality application such as hotels, restaurants and shops.


- ❑ Compact All-in-one M/B design with Rich I/O especially for POS Terminal
- ❑ Space saving and Silent Stand Alone All-in-one POS Terminal
- ❑ Pentium Celeron Mobile High Performance Platform
- ❑ Good Flexibility Design suitable for various applications
- ❑ With 12", 15" or 17" LCD with Touch Screen
- ❑ Available with different Touch Panel Technology (5-wire resistive, SAW, Capacitive)
- ❑ Extremely Solid and Reliable structure
- ❑ Water spill resist
- ❑ Power Switch and LCD Brightness Control Panel on the rear
- ❑ Hidden Connector and Power Cable Design
- ❑ Optional Wi-Fi Wireless LAN for data transmission
- ❑ Optional CF Socket functionality for thin client application



Tilt Angle 0°~ 90°: Adapt to operation in any environment



Triple Track Magnetic Stripe Reader for membership management or operator identification



Removable Base and Wall Mounting capability with 75mm VSEA holes



Second Display can be integrated to the back side of the system.



Customer Display VFD type (2X20) VFD Customer Display can be integrated to the back side of the system



Easily arrange the cables inside the stand.



# DT Series

*The Best Touch Solution*



Specification		MODEL	DT-120	DT-150	DT-170
Motherboard	CPU Type	Intel Celeron M CPU / Intel Core 2 Duo M CPU			
	System Freq.	533 / 800MHz			
	Chipset	Intel 960GLE (965GME) + ICH8M			
	Memory	One DDRII SO-DIMM socket (200PIN DDRII 533/667 up to 4GB)			
	Video	Integrated Graphic Engine			
	Ethernet	10/100/1000Mbps LAN			
	Audio	Realtek ALC 662 audio			
Storage Device		2.5" IDE or SATA HDD x 1 Compact Flash II Socket x 1			
I/O Connector		Serial Port x 4 External + 2 Internal Parallel Port x 1 USB 2.0 Port x 4 External + 4 Internal PS/2 Mini-DIN Keyboard Port x 1 & Mouse Port x 1 VGA Port x 1 (for second screen) RJ-45 Ethernet Port x 1 RJ-12 Cash Drawer Port x 2 Audio Line-out Port x 1 & Mic-in Port x 1			
Expansion Slot		Mini PCI Slot x 1			
Monitor		12" XGA TFT LCD	15" XGA TFT LCD	17" SXGA TFT LCD	
Touch Screen		TW 5-wire or ELO Resistive Touch Screen (RS-232 or USB Interface)			
Power Supply		Ext. 75W Power Supply		Internal 200W Power Supply	
Dimension (mm)		304(W)x229(D)x302(H)	380(W)x240(D)x317(H)	392(W)x240(D)x383(H)	
Optical Integrated Device		VFD Customer Display, MSR Card Reader, 3-in-1 Hybrid Card Reader Second 12"/15"/17" LCD Screen with or without Touch Screen Sound Speaker (DT-120 only)			